

## Product Data Sheet

### UOS RX

- **Description**

UOS RX motorcycle lubricant uses selected high-performance synthetic base oil and high viscosity index hydrogenation technology base oil. It's combined with advanced additives for four-stroke motorcycles. It has extraordinary anti-wear, cleaning and anti-oxidation properties and viscosity stability.

- **Application**

- Reduces engine wear and extends engine life.
- Protects engine under severe operating conditions.
- Retards harmful deposit formation on vital engine parts.
- Protects against rust and corrosion.

- **Characteristics**

Test	Method	Unit	5W-40	5W-50	10W-40	10W-50	15W-40
SAE Viscosity Grade	SAE J 300	-	<b>5W-40</b>	<b>5W-50</b>	<b>10W-40</b>	<b>10W-50</b>	<b>15W-40</b>
Density @ 15 °C	ASTM D 4052	kg/L	0.843	0.845	0.964	0.860	0.872
Flash Point	ASTM D 92	°C	220	222	220	224	226
Pour Point	ASTM D 97	°C	-42	-39	-33	-36	-27
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	89.17	115.2	97.33	131.1	116.9
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.96	18.37	14.77	18.93	14.99
Viscosity Index	ASTM D 2270	-	177	178	158	164	133
TBN	ASTM D 2896	mgKOH/g	7.0	7.0	7.0	7.0	6.5
CCS	ASTM D 5293	cP	≤6600	≤6600	≤7000	≤7000	-

- **Recommendations**

- API SP
- JASO MA2 (except for 5W-40)
- JASO MB (5W-40 only)