

Product Data Sheet

UOS CVTF INFINITY

- **Description**

It's blended with high-performance base oils & additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents.

- **Application**

- Fit a wide variety of seal.
- Excellent properties of anti-wear and oil film thickness.
- Outstanding performance of friction, oxidation, thermal and shear stability.
- Superior low-temperature fluidity reduces the start-up wear.

- **Characteristics**

Test	Method	Unit	INFINITY
Density @ 15 °C	ASTM D 4052	kg/L	0.854
Flash Point	ASTM D 92	°C	190
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	35.99
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	7.21
Viscosity Index	ASTM D 2270	-	169
Brookfield Viscosity @ -40°C	ASTM D 2983	mPa.s	14330

- **Recommendations**

- VW/AUDI G 052 180 A2, G 052 162 A2
- BMW 83 22 0 136 376, 83 22 0 429 154
- MINI/PUNCH EZL 799, 799A
- CHRYSLER CVTF+4 05191184A

● **Recommendations**

- DAIHATSU AMMIX CVT-DFE/DTC
- DODGE/JEEP NS-2
- FORD XT-7-QCFT, WSS-M2C933-A(CFT30), MERCON C(CFT30), CFT23
- GM 19260800, DEX-CVT
- SUZUKI CVTF-GREEN 1, GREEN-2, NS-2
- HONDA 08200-HCF2, 08200-9006, HMMF(WITHOUT STARTING CLUTCH)
- MAZDA CVTF 3320
- MINI COOPER EZL 799, 799A, 83 22 0 136 376, ZF CVT V1
- MITSUBISHI CVTF-J1, CVTF-J4
- NISSAN NS-1, NS-2, NS-3
- RENAULT ELFMATIC
- SATURN 22688912
- SUBARU LINEARTRONIC CVTF, K0421Y0700, K0415YA090, K0425Y0710, E-CVTF, i-CVTF, CV30, K0421Y0700, CVTF-II, K0425Y0711
- TOYOTA/LEXUS FE, TC