

Product Data Sheet

UOS ATF MB9

- **Description**

It's formulated by using fully synthetic technology, and to meet the demands of ZF 9HP automatic gearboxes. Its formulation is with the latest additives that ensures the characteristic of excellent oxidation stability and constant friction for a wide variety requirements of 9-speed automatic transmission. It provides the hassle free & smoothly running auto transmission all year round, and thus extended service life of bearings & gears.

- **Application**

- Excellent viscosity stability in operation.
- Fluidity performed & enhanced well at very low operation.
- Outstanding performance of oxidation and thermal stability.
- Excellent protection of rust, corrosion and wear.

- **Characteristics**

Test	Method	Unit	MB9
Density @ 15 °C	ASTM D 4052	kg/L	0.836
Flash Point	ASTM D 92	°C	208
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	27.2
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	5.96
Viscosity Index	ASTM D 2270	-	174

- **Recommendations**

- BENTLEY PY112995PA
- BMW 83 22 0 397114, 83 22 2 152 426, 83 22 2 289 720, 83 22 2 163 514, 83 22 2 305 396/397, 83 22 2 355 599, 83 22 2 355 601

● **Recommendations**

- CHRYSLER/DODGE/JEEP 68043742AA
- GM AW1 19256039/88863400/88863401, GMW 16444/16974
- HONDA 08200-9008, 08200-9016-A, 08200-9017
- HYUNDAI/KIA SP4-M1, SPH-IV, NWS 9638 T-5, 040000C90SG
- ISUZU 2-90531-200-0
- JAGUAR 02JDE 26444, 8432
- LAND ROVER LR023288, LR023289, LR0022460, TYK500050
- MASERATI 231603
- MAZDA ATF FZ
- MB 236.12, 236.14, 236.15, 236.17, 236.41
- MITSUBISHI ATF J3, ATF-MA1, ATF-PA, IV-SP
- NISSAN MATIC R/S/W
- PORSCHE 000 043 304 00/01, 000 043 305 43/54, 000 043 306 24, 958 300 540 00
- SAAB 93 165 147
- SUBARU ATF WS
- VW/AUDI G 052 533, G 055 005 A2, G 055 162 A2/A6, G 055 540 A2, G 060 162 A2
- VOLVO 31256774, 31256775