

Product Data Sheet

UOS ATF ZF8

- **Description**

It's formulated by using fully synthetic technology, with selected base stock and latest additives, that provides excellent service in applications for low and ultra-low viscosity ATF.

- **Application**

- To be used in low viscosity & ultra-low viscosity auto transmission.
- Supreme rust and corrosion protection.
- Enhanced fluidity for the low temperature service.
- Provide excellent oxidation and thermal stability for the life last longer.

- **Characteristics**

Test	Method	Unit	ZF8
Density @ 15 °C	ASTM D 4052	kg/L	0.845
Flash Point	ASTM D 92	°C	198
Pour Point	ASTM D 97	°C	-45
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	26.72
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	5.66
Viscosity Index	ASTM D 2270	-	160

- **Recommendations**

- MAZADA FZ
- GM/GMC/OPEL/SATURN AW1, VI, 88863400, 88863401
- MITSUBISHI ATF J3
- NISSAN/INFINITI MATIC-S
- HONDA/ACURA DW-1
- BMW/MINI 83 22 0 397 114



● Recommendations

- SAAB 93 165 147 - AW-1
- HYUNDAI/KIA NWS 9638 T-5, SP-IV, SPH-IV, SP4-M
- TOYOTA/LEXUS/SCION TYPE WS
- CHRYSLER/DODGE/JEEP 68043742AA
- VW/AUDI G 055 540 A2, G 060162 A1/A2/A6
- FORD/LINCOLN/MERCURY XT-10-QLV (LV)
- LAND ROVER LR023288
- ZF LIFEGUARDFLUID 8
- PORSCHE 000 043 304 00
- MB 236.12/14/15/41
- JAGUAR 02JDE 26444
- MASERATI 231603